

## TECHNICAL DATA SHEET N° 267

Code 0.534.1010

# **Linea Start Lavabile**

washable latex paint for interior

#### **GENERAL PROPERTIES**

Washable wall latex paint with an optimum whiteness and covering power. The product has a good applicability and flows perfectly, together with a good refinishing performance.

Specifically recommended for matt and consistent finishes on interior supports.

#### **INSTRUCTIONS**

# Substrate preparation

- Bare interior walls: remove by soft brush dust, filth & unsound plaster. Level any imperfections (holes, cracks & fissures) with stucco paste LITOSTUCCO or with powder stucco SILVER STUCK, working with shavings as needed. Allow 6 hours after the last one, sand stucco parts and clean properly, seal all the surface applying one hand of ISOLEX W or ARDFIX previously diluted. Allow 4 hours and apply two hands of LINEA START LAVABILE.
- Interior walls with distemper paintwork: clean the surface thoroughly, removing dust and filth. and stucco any imperfections with LITOSTUCCO, proceeding as described above. After sanding, seal all the surface with one hand of ISOLEX W or ARDFIX, allow 4 hours and apply LINEA START LAVABILE.
- Interior walls with washable emulsion paintwork: clean the surface thoroughly, stucco any imperfections, sand and dust. Seal repair areas with a coat of ARDFIX; allow 4 hours and apply LINEA START LAVABILE.

#### **Application**

LINEA START LAVABILE can be applied with the following tools and ways:

- Brush: for the first coat dilute at 30-35% in water volume, at 20-30 % for the second coat.
- Roller: dilute at 15-25% in water volume.
- Airless Spray gun: dilute approx. at 20-25% in water volume using a 0,25 mm Ø nozzle.
- LINEA START LAVABILE is compatible with the colourants at high concentration COLORATUTTO.
- Do not apply at air or substrate temperature below +5°C or above +35°C
- Wash tools immediately after use with water.
- Store in cool premises, under frost proof conditions.
- Use in compliance with the current Health & Safety regulations; dispose of spent material/containers according to the same.
  Refer to the MSDS for further information.
- LINEA START LAVABILE is a product suitable to be colored with 16COLOURS tinting system.

### **TECHNICAL DATA**

SPECIFIC WEIGHT		1620 ± 50 g/l
VISCOSITY AT 20°C		10000± 2000 cP
ASPECT		matt
Colour		white
DRYING AT 20° C	TOUCH DRY	2 h
	THROUGH DRYING	24 h
WASH RESISTANCE	EN 13300	Class 3

**YIELD** 

The two-coat painting cycle implies a yield of  $5 - 5.5 \text{ m}^2/\text{I}$ .

# **ITEM**

# TENDER SPECIFICATION WASHABLE LATEX PAINT FOR INTERIOR

Application on treated interior surfaces of two layers of washable high covering power based on synthetic copolymers in aqueous dispersion and colourant pigments type LINEA START LAVABILE, with a min. consumption of 0,18 l/m<sup>2</sup>. €/m².

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide. Revision 2021/12

