



Code 0.546.1010

Linea Start Traspirante

Matt latex paint for interior

GENERAL PROPERTIES

Matt breathable wall paint for interior with high covering power and a good whiteness, an optimum water vapor permeability, anti-reflective feature. It is specifically recommended for smooth and consistent finishes on interior supports.

INSTRUCTIONS

Substrate preparation

- Bare interior walls: remove by soft brush dust, filth & unsound plaster. Level any imperfections (holes, cracks & fissures) with LITOSTUCCO, working with shavings as needed.
Allow 6 hours after the last one, sand stucco parts and clean properly, seal all the surface applying one hand of ISOLEX W or ARDFIX previously diluted: when the surface is perfectly dry apply two hands of LINEA START TRASPIRANTE.
- Interior walls with distemper paintwork: clean the surface thoroughly, removing dust and filth. and stucco any imperfections with LITOSTUCCO, proceeding as described above. After sanding, seal the stuccoed areas with one hand of ISOLEX W or ARDFIX. Allow 4 hrs & apply LINEA START TRASPIRANTE.
- Interior walls with washable emulsion paintwork: clean the surface thoroughly, stucco any imperfections, sand and dust. Seal repair areas with a coat of ARDFIX; allow 4 hours and apply LINEA START TRASPIRANTE.

Application

LINEA START TRASPIRANTE can be applied with the following tools and ways:

- Brush: for the first coat dilute at 30-40% in water volume, at 25-35% for the second coat.
- Roller: dilute at 20-30% in water volume.
- Airless Spray gun: dilute approx. at 25-35% in water volume using a 0,25 mm Ø nozzle.
- LINEA START TRASPIRANTE is compatible with the universal colourants COLORATUTTO series 0.951
- Store in cool premises, under frost proof conditions.
- Wash tools immediately after use with water.
- Do not apply at air or substrate temperature below +5°C or above +35°C.
- Use in compliance with the current Health & Safety regulations; dispose of spent material/containers according to the same. Refer to the MSDS for further information.
- LINEA START TRASPIRANTE is a product suitable to be colored with 16COLOURS tinting system.

TECHNICAL DATA

SPECIFIC WEIGHT	1690 ± 50 g/l
VISCOSITY AT 20°C	20.000 ± 3000 cP
ASPECT	Matt
COLOUR	White
DRYING AT 20° C	TOUCH DRY 2 h
	THROUGH DRYING 24 h

YIELD

The two-coat painting cycle implies a yield of approx 4,5-5 m²/l. The yield may increase on rougher/more absorbent surfaces. It is better to determine the same by testing on the specific support.

TENDER SPECIFICATION ITEM

MATT LATEX PAINT FOR INTERIOR

Application on treated interior surfaces of two layers of matt latex wall paint for interior based on synthetic copolymerse and covering pigments type LINEA START TRASPIRANTE with a min. consumption of 0,2 l/m².
€/m².

The data herein were correct at the time of Quality Control and refer to standardized environmental conditions. The same are to be considered as a guide.
Revision 2021/12



ard raccanello s.p.a.

35129 PADOVA – Zona Ind.le Nord 1^a Strada, 13 – Tel. 049.8060000 (5 linee)
Fax 049.773749 – www.ard-raccanello.it - E-mail: assistenza@ard-raccanello.it